

# LOFT DESIGN

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres porcellanato - porcelain tiles

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>LOFT DESIGN</b>
FORMATI-SIZES :	<b>6x25</b>
NOMI-NAMES:	<b>LOFT IRON - LOFT DUST - LOFT VANILLA - LOFT BRICKY - LOFT WHITE</b>
COLORI-COLOURS :	<b>ANTRACITE - GRIGIO - BEIGE - ROSSO - BIANCO</b> <b>DARK GREY - GREY - BEIGE - RED - WHITE</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS:	<b>5</b>

## ACCESSORI - ACCESSORIES










FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	
DECORI-DECORS:		GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno  
*Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile*

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B I a** - Class of **B I a**

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		<b>7</b>	UNI EN 101
RESIST.ABRASIONE DELLA SUPERFICIE- PEI <i>RESISTANCE TO SURFACE ABRASION-PEI</i>		<b>IV</b>	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO <i>THICKNESS IN REFERENCE TO THE SIZES</i>		<b>10 mm</b>	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		<b>R 11</b>	DIN 51130
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		<b>5</b>	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		<b>A-LA-HA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA <i>BENDING STRENGTH/BREAKING STRENGTH</i>		<b>&gt; 40 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		<b>≤ 0,5%</b>	EN ISO 10545-3